TESY
It's impressive

ANTICALC

GCV 50 44 16D B14 TBR



TIN Code	304899
Model	Anticalc 50
Real Volume	50 L
Height	0.608 m
Width	0.440 m
Depth	0.467 m
Rated power	1600/800 W
Heating time Δt 45K (15 - 60°C)	1:37/3:15 h:min
Annual consumption of electricity AEC	1392 kWh

Energy class	C
Diameter	440 mm
Load profile	M
V40	74 L
$T_{out\ of\ the\ box}$	60 °C
MAX40	88 L

Information

GCV 50 44 16D B14 TBR

Serie information

GCV 50 44 16D B14 TBR

The vertical electric water heaters of the Anticalc series have been developed for trouble-free, long-term and reliable operation in areas supplied with hard and highly mineralized and/or aggressive water. The Anticalc heating element works at low surface temperature, which limits the deposition of lime scale. The range offers models with storage capacity of 50 to 100 litres.

- INSUTECH - an in-house TESY technology for highly efficient insulation and extremely low heat losses
- Option for choosing between two degrees of electric power
- ECO position of the external regulator for cost efficient and prolonged operation
- RELIABLE ANTICORROSION PROTECTION due to CRYSTALTECH enamel coating of the water tank
- Freeze protection
- DURABLE BOND between the edges of the cylinder by PLASMA WELDING
- BILIGHT indication
  - Red light: Heating
  - Blue light: Ready to use