



NON-ENAMELED BUFFER TANKS FOR HEAT PUMP SYSTEMS
WITHOUT HEAT EXCHANGERS

V 160 60 ACF W

TIN Code	305433
Range	163
Net weight	40 kg
Insulation	50 mm
Heat losses ΔT 45K	49 W
Energy class	B
Maximum operational temperature	95 °C
Diameter	600 mm
Rated pressure	3 bar



Information

V 160 60 ACF W

- Optimal operation in heating and cooling mode.
- **ANTI-CONDENS SOLUTION.** Additional insulation around all inlets and outlets to prevent condensation in cooling mode.
- High Energy Efficiency Class B.
- 4 inlets and 4 outlets of G1 1/2 size providing high flow rate.
- Additional pockets for air ventilation and draining.
- Innovative stratification nozzles at all inlets and outlets.
- 2 thermosensor pockets.

Serie information

V 160 60 ACF W

Pufer rezervoari, specijalno dizajnirani da budu kompatibilni sa sistemima toplotne pumpe.

Asortiman obuhvata modele od 100 L, 160 L i 200 L, podne, bez izmenjivača toplote.

*Sve prikazane slike služe samo za ilustraciju. Stvarni proizvod može da varira zbog poboljšanja proizvoda.

Težine navedene na ovoj veb stranici su neto vrednosti samo za referentne svrhe. Stvarne težine proizvoda mogu da variraju zbog proizvodnih tolerancija.