




BELLISLIMO LITE CLOUD

GCR 50 27 12 E32 ECW



TIN Code	306339
Model	BelliSlimo Lite Cloud 50
Real Volume	40 L
Height	0.704 m
Width	0.490 m
Depth	0.280 m
Rated power	1200/1200 W
Mounting	Reversible
Heating time Δt 45K (15 - 60°C)	1:23 h:min



Control via internet	yes
Annual consumption of electricity AEC	1308 kWh
Energy class	B
Load profile	M
V40	81/71 L
T _{out} of the box	80/80 °C
MAX40	81/71 L
Design	Flat



Electric Water Heater with two water tanks and **REVERSIBLE** installation

CONTROL VIA INTERNET & PERSONALISED PROGRAMMING with MyTESY App

QUICK FIRST SHOWER: Quickly heats up water for your shower

BOOST FUNCTION: One-time heating up to the maximum temperature

VACATION MODE: Just set the time and the date and your BelliSlimo Lite will be ready for you

HIGHEST ENERGY CLASS in its category: Energy Class B

UP TO 18% ELECTRICITY SAVINGS on a weekly basis by **ECO SMART** self-learning mode

ENERGY CALCULATOR

NEUTRALISES GERMS IN THE WATER TANK by Automatic Antilegionella setting

SELF-DIAGNOSTICS SYSTEM helps identify potential device issues

ANTI-FREEZE protection

HIGH RELIABILITY AND SAFETY of the heating process by precise **CAPILLARY THERMOSTAT**

RELIABLE ANTICORROSION PROTECTION due to **CRYSTALTECH** enamel coating of the water tank and the Magnesium Anode

HIGH TEMPERATURE AND PRESSURE RESISTANCE with a stainless steel hot water pipe

DURABLE BOND between the edges of the water tanks by **PLASMA WELDING**

PRESSURE RELIEF VALVE to prevent excess pressure build-up

HYGIENIC CERTIFICATE



Electric Water Heater with two water tanks and **REVERSIBLE** installation

CONTROL VIA INTERNET & PERSONALISED PROGRAMMING with MyTESY App

QUICK FIRST SHOWER: Quickly heats up water for your shower

BOOST FUNCTION: One-time heating up to the maximum temperature

VACATION MODE: Just set the time and the date and your BelliSlimo Lite will be ready for you

HIGHEST ENERGY CLASS in its category: Energy Class B

UP TO 18% ELECTRICITY SAVINGS on a weekly basis by **ECO SMART** self-learning mode

ENERGY CALCULATOR

NEUTRALISES GERMS IN THE WATER TANK by Automatic Antilegionella setting

SELF-DIAGNOSTICS SYSTEM helps identify potential device issues

ANTI-FREEZE protection

HIGH RELIABILITY AND SAFETY of the heating process by precise **CAPILLARY THERMOSTAT**

RELIABLE ANTICORROSION PROTECTION due to **CRYSTALTECH** enamel coating of the water tank and the Magnesium Anode

HIGH TEMPERATURE AND PRESSURE RESISTANCE with a stainless steel hot water pipe

DURABLE BOND between the edges of the water tanks by **PLASMA WELDING**

PRESSURE RELIEF VALVE to prevent excess pressure build-up

HYGIENIC CERTIFICATE